

Package ‘bmlm’

July 22, 2025

Title Bayesian Multilevel Mediation

Version 1.3.15

Date 2023-09-25

Description Easy estimation of Bayesian multilevel mediation models with Stan.

URL <https://github.com/mvuorre/bmlm/>

BugReports <https://github.com/mvuorre/bmlm/issues/>

License GPL (>= 3)

LazyData true

NeedsCompilation yes

Depends R (>= 3.4.0), Rcpp (>= 0.12.0)

Imports ggplot2 (>= 2.0.0), methods, RcppParallel (>= 5.0.1), rstan (>= 2.26.0), rstantools (>= 2.3.1.1)

Suggests qgraph, knitr, rmarkdown, reshape2, dplyr

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0), RcppParallel (>= 5.0.1), rstan (>= 2.26.0), StanHeaders (>= 2.26.0)

RoxygenNote 7.1.2

Encoding UTF-8

SystemRequirements GNU make

Biarch true

Author Matti Vuorre [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5052-066X>>)

Maintainer Matti Vuorre <m.j.vuorre@tilburguniversity.edu>

Repository CRAN

Date/Publication 2023-09-25 14:22:24 UTC

Contents

| | |
|------------------------------|---|
| bmlm-package | 2 |
| BLch9 | 2 |
| isolate | 3 |
| MEC2010 | 4 |
| mlm | 4 |
| mlm_pars_plot | 6 |
| mlm_path_plot | 7 |
| mlm_spaghetti_plot | 8 |
| mlm_summary | 9 |

| | |
|--------------|-----------|
| Index | 12 |
|--------------|-----------|

| | |
|--------------|---|
| bmlm-package | <i>bmlm: Easy estimation of Bayesian multilevel mediation models with Stan.</i> |
|--------------|---|

Description

See <https://mvuorre.github.io/bmlm/> for a short tutorial.

| | |
|-------|---|
| BLch9 | <i>Relationship between work stressors, work dissatisfaction, and relationship dissatisfaction.</i> |
|-------|---|

Description

Simulated data from Intensive Longitudinal Methods: An Introduction to Diary and Experience Sampling Research. (Bolger, & Laurenceau, 2013, chapter 9; <http://www.intensivelongitudinal.com/index.html>).

Usage

```
data(BLch9)
```

Format

A data frame with 2100 rows and 8 variables:

id ID of study participant
time Time
fwkstrs Number of work stressors
fwkdis Work dissatisfaction rating
freldis Relationship dissatisfaction
x Subject-mean deviated number of work stressors
m Subject-mean deviated work dissatisfaction rating
y Subject-mean deviated relationship dissatisfaction

Source

<http://www.intensivelongitudinal.com/datasets.html>

isolate *Create isolated within- (and optionally between-) person variables.*

Description

Creates variables that represent pure within- and between-person predictors.

Usage

```
isolate(d = NULL, by = NULL, value = NULL, z = FALSE, which = "within")
```

Arguments

| | |
|-------|--|
| d | A data.frame. |
| by | A vector of values in d by which the data is clustered. i.e. a vector of unique participant IDs. |
| value | Names of columns in d to isolate. Multiple values can be given by value = c("var1", "var2", "var3") |
| z | Should the created values be standardized (defaults to FALSE). |
| which | Which component to return. "within" (default) returns within-person deviations only; "between" returns between-person means only; "both" returns both. |

Value

A data.frame with additional columns for the within- and between-person variables. The new columns are labelled `_cw` for centered-within and `_cb` for centered-between.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
# Create within-person deviations of work stressors in BLch9.
data(BLch9)
BLch9 <- isolate(BLch9, by = "id", value = "fwkstrs")
head(BLch9) # Now has new column for within-person work stressors.
```

MEC2010

Judgments of performance in a video game

Description

Data from an experiment where participants rated their performance in a video game in two conditions. (Experiment 1 in Metcalfe, Eich, & Castel, 2010; <https://www.sciencedirect.com/science/article/pii/S0010027710001113>).

Usage

```
data(MEC2010)
```

Format

A data frame with 344 rows and 4 variables:

subj Subject id number.

lag Lag condition (0 = no lag, 1 = 250ms lag).

hr Hit rate.

jop Judgment of Performance.

Source

Metcalfe, J., Eich, T. S., & Castel, A. D. (2010). Metacognition of agency across the lifespan. *Cognition*, 116(2), 267-282. doi:10.1016/j.cognition.2010.05.009

mlm

Estimate a multilevel mediation model

Description

Estimates a Bayesian multilevel mediation model using Stan.

Usage

```
mlm(  
  d = NULL,  
  id = "id",  
  x = "x",  
  m = "m",  
  y = "y",  
  priors = NULL,  
  binary_y = FALSE,  
  ...  
)
```

Arguments

| | |
|-----------------------|---|
| <code>d</code> | A <code>data.frame</code> or a <code>data_frame</code> . |
| <code>id</code> | Column of participant IDs in data. |
| <code>x</code> | Column of X values in data. |
| <code>m</code> | Column of M values in data. |
| <code>y</code> | Column of Y values in data. |
| <code>priors</code> | A list of named values to be used as the prior scale parameters. See details. |
| <code>binary_y</code> | Set to <code>TRUE</code> if <code>y</code> is binary and should be modelled with logistic regression. Defaults to <code>FALSE</code> (<code>y</code> treated as continuous.) This feature is experimental. |
| <code>...</code> | Other optional parameters passed to <code>rstan::stan()</code> . |

Details

Draw samples from the joint posterior distribution of a multilevel mediation model using Stan.

Priors:

Users may pass a list of named values for the `priors` argument. The values will be used to define the scale parameter of the respective prior distributions. This list may specify some or all of the following parameters:

dy, dm Regression intercepts (for Y and M as outcomes, respectively.)

a, b, cp Regression slopes.

tau_x Varying effects SDs for above parameters (e.g replace `x` with `a`.)

lkj_shape Shape parameter for the LKJ prior.

See examples for specifying the following: Gaussian distributions with $SD = 10$ as priors for the intercepts, Gaussians with $SD = 2$ for the slopes, Half-Cauchy distributions with scale parameters 1 for the varying effects SDs, and an LKJ prior of 2.

Value

An object of S4 class `stanfit`, with all its available methods.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
## Not run:
## Run example from Bolger and Laurenceau (2013)
data(BLch9)
fit <- mlm(BLch9)
mlm_summary(fit)

### With priors
Priors <- list(dy = 10, dm = 10, a = 2, b = 2, cp = 2,
              tau_dy = 1, tau_dm = 1, tau_a = 1, tau_b = 1, tau_cp = 1,
```

```

      lkj_shape = 2)
fit <- mlm(BLch9, priors = Priors)

## End(Not run)

```

mlm_pars_plot

Plot estimated parameters of multilevel mediation model

Description

Plot the model's estimated parameters as histograms or a coefficient plot.

Usage

```

mlm_pars_plot(
  mod = NULL,
  type = "hist",
  color = "black",
  p_shape = 15,
  p_size = 1.2,
  level = 0.95,
  nrow = 3,
  pars = c("a", "b", "cp", "covab", "me", "c", "pme")
)

```

Arguments

| | |
|---------|--|
| mod | A Stanfit model estimated with <code>mlm()</code> . |
| type | Type of the plot, <code>hist</code> , <code>coef</code> , or <code>violin</code> . |
| color | Color (and fill) for plots. |
| p_shape | Shape of points for <code>coefplot</code> . |
| p_size | Size of points for <code>coefplot</code> . |
| level | X level for Credible Intervals. (Defaults to <code>.95</code> .) |
| nrow | Number of rows for multiple histograms. |
| pars | Which parameters to plot. |

Details

The point estimate for the coefficient plot is the posterior mean.

Value

A `ggplot2` object.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

mlm_path_plot

*Plot bmlm's mediation model as a path diagram***Description**

Plots a path diagram for an estimated multilevel mediation model.

Usage

```
mlm_path_plot(
  mod = NULL,
  xlab = "X",
  ylab = "Y",
  mlab = "M",
  level = 0.95,
  random = TRUE,
  text = FALSE,
  id = NULL,
  digits = 2,
  ...
)
```

Arguments

| | |
|--------|---|
| mod | A Stanfit model estimated with <code>mlm()</code> . |
| xlab | Label for X |
| ylab | Label for Y |
| mlab | Label for M |
| level | "Confidence" level for credible intervals. (Defaults to .95.) |
| random | Should the "random" effects SDs be displayed? (Default = TRUE) |
| text | Should additional parameter values be displayed? (Defaults to FALSE.) |
| id | Plot an individual-level path diagram by specifying ID number. |
| digits | Number of significant digits to show on graph. (Default = 2.) |
| ... | Other arguments passed on to <code>qgraph::qgraph()</code> . |

Details

Plots a path diagram of the mediation model, with estimated parameter values and credible intervals. Can also be used to draw a template diagram of the mediation model by not specifying input to the `mod` argument.

To modify various settings of the underlying `qgraph` object, see [qgraph](#).

Value

A `qgraph` object.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Examples

```
# Draw a template path diagram of the mediation model
mlm_path_plot()
```

mlm_spaghetti_plot *Plot fitted values of M and Y from multilevel mediation model*

Description

Plot population-level fitted values and X values, for M and Y.

Usage

```
mlm_spaghetti_plot(  
  mod = NULL,  
  d = NULL,  
  id = "id",  
  x = "x",  
  m = "m",  
  y = "y",  
  level = 0.95,  
  n = 12,  
  binary_y = FALSE,  
  mx = "fitted",  
  fixed = TRUE,  
  random = TRUE,  
  h_jitter = 0,  
  v_jitter = 0,  
  bar_width = 0.2,  
  bar_size = 0.75,  
  n_samples = NA  
)
```

Arguments

| | |
|-----|---|
| mod | A multilevel mediation model estimated with <code>mlm()</code> . |
| d | A <code>data.frame</code> or a <code>data_frame</code> used in fitting model. |
| id | Name of id variable (identifying subjects) in data (d). |
| x | Name of X variable in data. |
| m | Name of M variable in data. |
| y | Name of Y variable in data. |

| | |
|-----------|---|
| level | X level for Credible Intervals. (Defaults to .95.) |
| n | Number of points along X to evaluate fitted values on. See details. |
| binary_y | Set to TRUE if the outcome variable (Y) is 0/1. |
| mx | Should the X axis of the M-Y figure be "fitted" values, or "data" values. Defaults to "fitted". |
| fixed | Should the population-level ("fixed") fitted values be shown? |
| random | Should the subject-level ("random") fitted values be shown? |
| h_jitter | Horizontal jitter of points. Defaults to 0. |
| v_jitter | Vertical jitter of points. Defaults to 0. |
| bar_width | Width of the error bars. Defaults to 0.2. |
| bar_size | Thickness of the error bars. Defaults to 0.75. |
| n_samples | Number of MCMC samples to use in calculating fitted values. See details. |

Details

If $n = 2$, the fitted values will be represented as points with X line with a Confidence Ribbon instead. If a very large model is fitted with a large number of MCMC iterations, the function might take a long time to run. In these cases, users can set `n_samples` to a smaller value (e.g. 1000), in which case the fitted values (and the CIs) will be based on a random subset of `n_samples` MCMC samples. The default value is NA, meaning that all MCMC samples are used.

Value

A list of two `ggplot2` objects.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

mlm_summary

Print a summary of the estimated multilevel mediation model

Description

Prints the estimated parameters (numerical summaries of the marginal posterior distributions).

Usage

```
mlm_summary(
  mod = NULL,
  level = 0.95,
  pars = c("a", "b", "cp", "me", "c", "pme"),
  digits = 2
)
```

Arguments

| | |
|---------------------|--|
| <code>mod</code> | A <code>stanfit</code> object obtained from <code>mlm()</code> |
| <code>level</code> | "Confidence" level; Defines the limits of the credible intervals. Defaults to .95 (i.e. displays 95% CIs.) |
| <code>pars</code> | Parameters to summarize. Defaults to main average-level parameters. See Details for more information. |
| <code>digits</code> | How many decimal points to display in the output. Defaults to 2. |

Details

After estimating a model (drawing samples from the joint posterior probability distribution) with `mlm()`, show the estimated results by using `mlm_summary(fit)`, where `fit` is an object containing the fitted model.

The function shows, for each parameter specified with `pars`, the posterior mean, and limits of the Credible Interval as specified by `level`. For example, `level = .91` shows a 91% Credible Interval, which summarizes the central 91% mass of the marginal posterior distribution.

Parameters: By default, `mlm()` estimates and returns a large number of parameters, including the varying effects, and their associated standard deviations. However, `mlm_summary()` by default only displays a subset of the estimated parameters:

- a** Regression slope of the X -> M relationship.
- b** Regression slope of the M -> Y relationship.
- cp** Regression slope of the X -> Y relationship. (Direct effect.)
- me** Mediated effect ($a * b + \sigma_{a_j b_j}$).
- c** Total effect of X on Y. ($cp + me$)
- pme** Percent mediated effect.

The user may specify `pars = NULL` to display all estimated parameters. Other options include e.g. `pars = "tau"` to display the varying effects' standard deviations. To display all the group-level parameters (also known as random effects) only, specify `pars = "random"`. With this argument, `mlm_summary()` prints the following parameters:

- tau_a** Standard deviation of subject-level `a_js`.
- tau_b** Standard deviation of subject-level `b_js`.
- tau_cp** Standard deviation of subject-level `c\ '_js`.
- covab** Estimated covariance of `a_j` and `b_js`.
- corrab** Estimated correlation of `a_j` and `b_js`.

To learn more about the additional parameters, refer to the Stan code (`cat(get_stancode(fit))`).

Value

A data.frame summarizing the estimated multilevel mediation model:

- Parameter** Name of parameter
- Mean** Mean of parameter's posterior distribution.
- Median** Median of parameter's posterior distribution.

SE Standard deviation of parameter's posterior distribution.

ci_lwr The lower limit of Credible Intervals.

ci_upr The upper limit of Credible Intervals.

n_eff Number of efficient samples.

Rhat Should be 1.00.

Author(s)

Matti Vuorre <mv2521@columbia.edu>

Index

* datasets

BLch9, 2

MEC2010, 4

BLch9, 2

bmlm (bmlm-package), 2

bmlm-package, 2

isolate, 3

MEC2010, 4

mlm, 4

mlm_pars_plot, 6

mlm_path_plot, 7

mlm_spaghetti_plot, 8

mlm_summary, 9

qgraph, 7