

# Package ‘REDCapR’

October 12, 2022

**Title** Interaction Between R and REDCap

**Description** Encapsulates functions to streamline calls from R to the REDCap API. REDCap (Research Electronic Data CAPture) is a web application for building and managing online surveys and databases developed at Vanderbilt University. The Application Programming Interface (API) offers an avenue to access and modify data programmatically, improving the capacity for literate and reproducible programming.

**Version** 1.1.0

**URL** <https://ouhscbbmc.github.io/REDCapR/>,  
<https://github.com/OuhscBbmc/REDCapR>,  
<https://www.ouhsc.edu/bbmc/>, <https://project-redcap.org>

**BugReports** <https://github.com/OuhscBbmc/REDCapR/issues>

**Depends** R(>= 3.5.0)

**Imports** checkmate (>= 2.0), dplyr (>= 1.0), httr (>= 1.4.0), jsonlite,  
magrittr (>= 1.5), methods, readr (>= 2.0), rlang (>= 0.4),  
tibble (>= 2.0), tidyr (>= 1.0)

**Suggests** spelling, covr (>= 3.4), DBI (>= 1.1), kableExtra (>= 1.0),  
knitr (>= 1.18), odbc (>= 1.1.1), rmarkdown (>= 2.0),  
sessioninfo (>= 1.1.1), testthat (>= 3.0)

**License** MIT + file LICENSE

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 7.2.1

**Config/testthat/edition** 3

**Language** en-US

**NeedsCompilation** no

**Author** Will Beasley [aut, cre] (<<https://orcid.org/0000-0002-5613-5006>>),  
David Bard [ctb],  
Thomas Wilson [ctb],  
John J Aponte [ctb],

Rollie Parrish [ctb],  
 Benjamin Nutter [ctb],  
 Andrew Peters [ctb],  
 Hao Zhu [ctb] (<<https://orcid.org/0000-0002-3386-6076>>),  
 Janosch Linkersdörfer [ctb] (<<https://orcid.org/0000-0002-1577-1233>>),  
 Jonathan Mang [ctb] (<<https://orcid.org/0000-0003-0518-4710>>),  
 Felix Torres [ctb],  
 Philip Chase [ctb],  
 Victor Castro [ctb] (<<https://orcid.org/0000-0001-7390-6354>>)

**Maintainer** Will Beasley <[wibeasley@hotmail.com](mailto:wibeasley@hotmail.com)>

**Repository** CRAN

**Date/Publication** 2022-08-10 16:10:18 UTC

## R topics documented:

REDCapR-package . . . . .	3
collapse_vector . . . . .	4
constant . . . . .	5
create_batch_glossary . . . . .	7
kernel_api . . . . .	8
metadata_utilities . . . . .	9
redcap_arm_export . . . . .	11
redcap_column_sanitize . . . . .	12
redcap_dag_read . . . . .	13
redcap_delete . . . . .	15
redcap_download_file_oneshot . . . . .	17
redcap_download_instrument . . . . .	19
redcap_event_instruments . . . . .	21
redcap_instruments . . . . .	23
redcap_metadata_read . . . . .	24
redcap_metadata_write . . . . .	26
redcap_next_free_record_name . . . . .	28
redcap_project . . . . .	29
redcap_read . . . . .	30
redcap_read_oneshot . . . . .	34
redcap_read_oneshot_eav . . . . .	38
redcap_report . . . . .	41
redcap_survey_link_export_oneshot . . . . .	44
redcap_upload_file_oneshot . . . . .	46
redcap_users_export . . . . .	48
redcap_variables . . . . .	49
redcap_version . . . . .	51
redcap_write . . . . .	52
redcap_write_oneshot . . . . .	54
replace_nas_with_explicit . . . . .	56
retrieve_credential . . . . .	57
sanitize_token . . . . .	60

<i>REDCapR</i> -package	3
validate . . . . .	61
<b>Index</b>	<b>63</b>

REDCapR-package      *R utilities for interacting with a REDCap data system* <https://www.project-redcap.org/>

## Description

Comprehensive documentation is also available at <https://ouhscbbmc.github.io/REDCapR/>.

Much of this package has been developed to support the needs of the following projects. We appreciate the support.

- *OUHSC CCAN Independent Evaluation of the State of Oklahoma Competitive Maternal, Infant, and Early Childhood Home Visiting (MIECHV) Project*. HRSA/ACF D89MC23154. David Bard, PI, OUHSC; 2011-2015.
- *Independent Evaluation of the State of OK MIECHV Evidence Based Home Visitation Project*, NIH-sponsored collaboration with **OSDH**. David Bard, PI, OUHSC; 2015-2017.
- *OSDH ParentPRO Pilot Evaluation*, federally-sponsored collaboration with **OSDH**. David Bard, PI, OUHSC; 2015-2017.
- *Title IV-E Waiver Project*, **HRSA/MCHB**-sponsored collaboration with **OKDHS**; David Bard, PI, OUHSC; 2014-2017.
- *Integrative Analysis of Longitudinal Studies of Aging (IALSA)*, sponsored by **NIH 5P01AG043362**. Scott Hofer, PI, University of Victoria; Will Beasley, PI of site-award, OUHSC; 2013-2018.
- *Oklahoma Shared Clinical and Translational Resources*, sponsored by **NIH NIGMS; U54 GM104938**. Judith A. James, PI, OUHSC; 2013-2018.
- Additional Institutional Support from OUHSC **Dept of Pediatrics**; 2013-2017.

## Note

The release version is available through **CRAN** by running `install.packages('REDCapR')`. The most recent development version is available through **GitHub** by running `remotes::install_github('OuhscBbmc/REDCapR')` (make sure **remotes** is already installed). If you're having trouble with the package, please install the development version. If this doesn't solve your problem, please create a **new issue**, or email Will.

See REDCapR's advanced vignette for information and examples for overriding the default SSL options.

## Examples

```
## Not run:
# Install/update REDCapR with the release version from CRAN.
install.packages('REDCapR')

# Install/update REDCapR with the development version from GitHub
```

```
# install.packages("remotes") # Uncomment if `remotes` isn't installed already.
remotes::install_github('OuhscBbmc/REDCapR')

## End(Not run)
```

---

collapse_vector	<i>Collapse a vector of values into a single string when necessary</i>
-----------------	--

---

### Description

REDCap's API frequently specifies a series of values separated by commas. In the R world, it's easier to keep these values as separate elements in a vector. This functions squashes them together in a single character element (presumably right before the return value is passed to the API)

### Usage

```
collapse_vector(elements, collapsed)
```

### Arguments

elements	An array of values. Can be NULL. Required.
collapsed	A single character element, where the values are separated by commas. Can be NULL. Required.

### Value

A single character element, where the values are separated by commas. Can be blank. (*i.e.*, "").

### Author(s)

Will Beasley

### Examples

```
library(REDCapR) #Load the package into the current R session.
REDCapR::collapse_vector(elements=NULL, collapsed=NULL)
REDCapR::collapse_vector(elements=letters, collapsed=NULL)
REDCapR::collapse_vector(elements=NULL, collapsed="4,5,6")
```

---

constant	<i>Collection of REDCap-specific constants</i>
----------	--

---

## Description

Collection of constants defined by the REDCap developers.

## Usage

```
constant(name)
```

## Arguments

name	Name of constant. Required character.
------	---------------------------------------

## Details

### Form Completeness

The current constants relate to the 'complete' variable at the end of each form.

- `form_incomplete`: 0L (*i.e.*, an integer)
- `form_unverified`: 1L
- `form_complete`: 2L

### Export Rights

See [https://your-server/redcap/api/help/?content=exp\\_users](https://your-server/redcap/api/help/?content=exp_users).

- `data_export_rights_no_access`: 0L
- `data_export_rights_deidentified`: 1L
- `data_export_rights_full`: 2L

### Form Rights

See [https://your-server/redcap/api/help/?content=exp\\_users](https://your-server/redcap/api/help/?content=exp_users). The order of these digits may be unexpected.

- `form_rights_no_access`: 0L
- `form_rights_readonly`: 2L
- `form_rights_edit_form`: 1L
- `form_rights_edit_survey`: 3L

### Access Rights

See [https://your-server/redcap/api/help/?content=exp\\_users](https://your-server/redcap/api/help/?content=exp_users).

- `access_no`: 0L
- `access_yes`: 1L

To add more, please for and edit `constant.R` on GitHub and submit a pull request. For instructions, please see [Editing files in another user's repository # nolint](#) in the GitHub documentation.

**Value**

The constant's value. Currently all are single integers, but that could be expanded in the future.

**Author(s)**

Will Beasley

**Examples**

```

REDCapR::constant("form_incomplete") # Returns 0L
REDCapR::constant("form_unverified") # Returns 1L
REDCapR::constant("form_complete" ) # Returns 2L

REDCapR::constant("data_export_rights_no_access" ) # Returns 0L
REDCapR::constant("data_export_rights_deidentified") # Returns 1L
REDCapR::constant("data_export_rights_full" ) # Returns 2L

REDCapR::constant("form_rights_no_access") # Returns 0L
REDCapR::constant("form_rights_readonly" ) # Returns 2L --Notice the order
REDCapR::constant("form_rights_edit_form") # Returns 1L
REDCapR::constant("form_rights_edit_survey") # Returns 3L

REDCapR::constant("access_no" ) # Returns 0L
REDCapR::constant("access_yes") # Returns 1L

REDCapR::constant(c(
  "form_complete",
  "form_complete",
  "form_incomplete"
)) # Returns c(2L, 2L, 0L)
REDCapR::constant(c(
  "form_rights_no_access",
  "form_rights_readonly",
  "form_rights_edit_form",
  "form_rights_edit_survey"
)) # Returns c(0L, 2L, 1L, 3L)

constant_to_form_completion( c(0, 2, 1, 2, NA))
constant_to_form_rights( c(0, 2, 1, 2, NA))
constant_to_export_rights( c(0, 2, 1, 3, NA))
constant_to_access( c(0, 1, 1, 0, NA))

## Not run:
# The following line returns an error:
# Assertion on 'name' failed: Must be a subset of
# {'form_complete','form_incomplete','form_unverified'},
# but is {'bad-name'}.

REDCapR::constant("bad-name") # Returns an error

REDCapR::constant(c("form_complete", "bad-name")) # Returns an error

```

```
## End(Not run)
```

---

create\_batch\_glossary *Creates a dataset that help batching long-running read and writes*

---

## Description

The function returns a `base::data.frame()` that other functions use to separate long-running read and write REDCap calls into multiple, smaller REDCap calls. The goal is to (1) reduce the chance of time-outs, and (2) introduce little breaks between batches so that the server isn't continually tied up.

## Usage

```
create_batch_glossary(row_count, batch_size)
```

## Arguments

<code>row_count</code>	The number records in the large dataset, before it's split.
<code>batch_size</code>	The maximum number of subject records a single batch should contain.

## Details

This function can also assist splitting and saving a large `base::data.frame()` to disk as smaller files (such as a .csv). The padded columns allow the OS to sort the batches/files in sequential order.

## Value

Currently, a `base::data.frame()` is returned with the following columns,

- `id`: an integer that uniquely identifies the batch, starting at 1.
- `start_index`: the index of the first row in the batch. `integer`.
- `stop_index`: the index of the last row in the batch. `integer`.
- `id_pretty`: a character representation of `id`, but padded with zeros.
- `start_index_pretty`: a character representation of `start_index`, but padded with zeros.
- `stop_index_pretty`: a character representation of `stop_index`, but padded with zeros.
- `label`: a character concatenation of `id_pretty`, `start_index_pretty`, and `stop_index_pretty`.

## Author(s)

Will Beasley

## See Also

See `redcap_read()` for a function that uses `create_batch_gloassary`.

**Examples**

```

REDCapR::create_batch_glossary(100, 50)
REDCapR::create_batch_glossary(100, 25)
REDCapR::create_batch_glossary(100, 3)
d <- data.frame(
  record_id = 1:100,
  iv       = sample(x=4, size=100, replace=TRUE),
  dv       = rnorm(n=100)
)
REDCapR::create_batch_glossary(nrow(d), batch_size=40)

```

---

kernel\_api

*REDCapR internal function for calling the REDCap API*


---

**Description**

This function is used by other functions to read and write values.

**Usage**

```

kernel_api(
  redcap_uri,
  post_body,
  config_options,
  encoding = "UTF-8",
  content_type = "text/csv"
)

```

**Arguments**

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
post_body	List of contents expected by the REDCap API. Required.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.
encoding	The encoding value passed to <code>httr::content()</code> . Defaults to 'UTF-8'.
content_type	The MIME value passed to <code>httr::content()</code> . Defaults to 'text/csv'.

**Details**

If the API call is unsuccessful, a value of `base::package_version("0.0.0")` will be returned. This ensures that the function will always return an object of class `base::package_version`. It guarantees the value can always be used in `utils::compareVersion()`.

**Value**

A `utils::packageVersion`.



**Examples**

```

config_options <- NULL
uri           <- "https://bbmc.ouhsc.edu/redcap/api/"
token        <- "9A81268476645C4E5F03428B8AC3AA7B"
post_body    <- list(
  token      = token,
  content    = 'project',
  format     = 'csv'
)
## Not run:
kernel <- REDCapR::kernel_api(uri, post_body, config_options)

# Consume the results in a few different ways.
kernel$result
read.csv(text=kernel$raw_text)
as.list(read.csv(text=kernel$raw_text))

## End(Not run)

```

---

metadata\_utilities      *Manipulate and interpret the metadata of a REDCap project*

---

**Description**

A collection of functions that assists handling REDCap project metadata.

**Usage**

```

regex_named_captures(pattern, text, perl = TRUE)

checkbox_choices(select_choices)

```

**Arguments**

pattern	The regular expression pattern. Required.
text	The text to apply the regex against. Required.
perl	Indicates if perl-compatible regexps should be used. Default is TRUE. Optional.
select_choices	The text containing the choices that should be parsed to determine the id and label values. Required.

**Details**

The `regex_named_captures()` function is general, and not specific to REDCap; it accepts any arbitrary regular expression. It returns a `base::data.frame()` with as many columns as named matches.

The `checkbox_choices()` function is specialized, and accommodates the "select choices" for a *single* REDCap checkbox group (where multiple boxes can be selected). It returns a `base::data.frame()` with two columns, one for the numeric id and one for the text label.

**Value**

Currently, a `base::data.frame()` is returned a row for each match, and a column for each *named* group within a match. For the `retrieve_checkbox_choices()` function, the columns will be.

- `id`: The numeric value assigned to each choice (in the data dictionary).
- `label`: The label assigned to each choice (in the data dictionary).

**Author(s)**

Will Beasley

**References**

See the official documentation for permissible characters in a checkbox label. *I'm bluffing here, because I don't know where this is located. If you know, please tell me.*

**Examples**

```
# The weird ranges are to avoid the pipe character;
# PCRE doesn't support character negation.
pattern_boxes <- "(?<=\\A| \\| )(?<id>\\d{1,}), (?<label>[\\x20-\\x7B\\x7D-\\x7E]{1,})(?= \\| |\\Z)"

choices_1 <- paste0(
  "1, American Indian/Alaska Native | ",
  "2, Asian | ",
  "3, Native Hawaiian or Other Pacific Islander | ",
  "4, Black or African American | ",
  "5, White | ",
  "6, Unknown / Not Reported")

# This calls the general function, and requires the correct regex pattern.
REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_1)

# This function is designed specifically for the checkbox values.
REDCapR::checkbox_choices(select_choices=choices_1)

## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"

ds_metadata <- redcap_metadata_read(redcap_uri=uri, token=token)$data
choices_2 <- ds_metadata[ds_metadata$field_name=="race", "select_choices_or_calculations"]

REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_2)

## End(Not run)

path_3    <- system.file(package="REDCapR", "test-data/project-simple/simple-metadata.csv")
ds_metadata_3 <- read.csv(path_3)
choices_3 <- ds_metadata_3[ds_metadata_3$field_name=="race", "select_choices_or_calculations"]
REDCapR::regex_named_captures(pattern=pattern_boxes, text=choices_3)
```

---

redcap_arm_export	<i>Export Arms</i>
-------------------	--------------------

---

### Description

Export Arms of a REDCap project

### Usage

```
redcap_arm_export(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

### Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <a href="#">redcap_read_one_shot()</a> . Optional.

### Value

Currently, a list is returned with the following elements:

- `has_arms`: a logical value indicating if the REDCap project has arms (*i.e.*, "TRUE") or is a classic non-longitudinal project (*i.e.*, "FALSE").
- `data`: a [tibble](#) with one row per arm. The columns are `arm_number` (an integer) and `arm_name` (a human-friendly string).
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"

# Query a classic project with 3 arms
token_1 <- "CDF9F3767E413FDBAA31D92E9F36730A"
result_1 <- REDCapR::redcap_arm_export(redcap_uri=uri, token=token_1)
result_1$has_arms
result_1$data

# Query a classic project without arms
token_2 <- "D70F9ACD1EDD6F151C6EA78683944E98"
result_2 <- REDCapR::redcap_arm_export(redcap_uri=uri, token=token_2)
result_2$has_arms
result_2$data

## End(Not run)
```

---

```
redcap_column_sanitize
```

*Sanitize to adhere to REDCap character encoding requirements*

---

**Description**

Replace non-ASCII characters with legal characters that won't cause problems when writing to a REDCap project.

**Usage**

```
redcap_column_sanitize(
  d,
  column_names = colnames(d),
  encoding_initial = "latin1",
  substitution_character = "?"
)
```

**Arguments**

<code>d</code>	The <code>base::data.frame()</code> containing the dataset used to update the REDCap project. Required.
<code>column_names</code>	An array of character values indicating the names of the variables to sanitize. Optional.
<code>encoding_initial</code>	An array of character values indicating the names of the variables to sanitize. Optional.
<code>substitution_character</code>	The character value that replaces characters that were unable to be appropriately matched.

## Details

Letters like an accented 'A' are replaced with a plain 'A'.

This is a thin wrapper around `base::iconv()`. The ASCII//TRANSLIT option does the actual transliteration work. As of R 3.1.0, the OSes use similar, but different, versions to convert the characters. Be aware of this in case you notice OS-dependent differences.

## Value

A `base::data.frame()` with same columns, but whose character values have been sanitized.

## Author(s)

Will Beasley

## Examples

```
# Typical examples are not shown because they require non-ASCII encoding,  
# which makes the package documentation less portable.
```

```
dirty <- data.frame(  
  id = 1:3,  
  names = c("Ekstr\x8m", "J\x6reskog", "bi\xdfchen Z\xfccher")  
)
```

```
REDCapR::redcap_column_sanitize(dirty)
```

---

redcap_dag_read	<i>Read data access groups from a REDCap project</i>
-----------------	--

---

## Description

This function reads all available data access groups from REDCap and returns them as a `base::data.frame()`.

## Usage

```
redcap_dag_read(  
  redcap_uri,  
  token,  
  http_response_encoding = "UTF-8",  
  locale = readr::default_locale(),  
  verbose = TRUE,  
  config_options = NULL  
)
```

**Arguments**

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
http_response_encoding	The encoding value passed to <code>httr::content()</code> . Defaults to 'UTF-8'.
locale	a <code>readr::locale()</code> object to specify preferences like number, date, and time formats. This object is passed to <code>readr::read_csv()</code> . Defaults to <code>readr::default_locale()</code> .
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package.

**Value**

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of all data access groups of the project.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_codes`: A collection of `http status codes`, separated by semicolons. There is one code for each batch attempted.
- `outcome_messages`: A collection of human readable strings indicating the operations' semicolons. There is one code for each batch attempted. In an unsuccessful operation, it should contain diagnostic information.
- `elapsed_seconds`: The duration of the function.

**Author(s)**

Jonathan M. Mang

**References**

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_dag_read(redcap_uri=uri, token=token)$data

## End(Not run)
```

---

redcap_delete	<i>Delete records in a REDCap project</i>
---------------	---

---

### Description

Delete existing records by their ID from REDCap.

### Usage

```
redcap_delete(
  redcap_uri,
  token,
  records_to_delete,
  arm_of_records_to_delete = NULL,
  verbose = TRUE,
  config_options = NULL
)
```

### Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records_to_delete	A character vector of the project's record_id values to delete. Required.
arm_of_records_to_delete	A single integer reflecting the arm containing the records to be deleted. Leave it as NULL if the project has no arms and is not longitudinal. Required if the REDCap project has arms. See Details below.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <a href="#">redcap_read_oneshot()</a> . Optional.

### Details

REDCap requires that at least one record\_id value be passed to the delete call.

When the project has arms, REDCapR has stricter requirements than REDCap. If the REDCap project has arms, a value must be passed to `arm_of_records_to_delete`. This is a different behavior than calling the server through `cURL` –which if no arm number is specified, then all arms are cleared of the specified record\_ids.

Note that all longitudinal projects technically have arms, even if only one arm is defined. Therefore a value of `arm_number` must be specified for all longitudinal projects.

## Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

## Author(s)

Jonathan Mang, Will Beasley

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

## Examples

```
## Not run:
records_to_delete <- c(102, 103, 105, 120)

# Deleting from a non-longitudinal project with no defined arms:
REDCapR::redcap_delete(
  redcap_uri      = uri,
  token          = token,
  records_to_delete = records_to_delete,
)

# Deleting from a project that has arms or is longitudinal:
arm_number <- 2L # Not the arm name
REDCapR::redcap_delete(
  redcap_uri      = uri,
  token          = token,
  records_to_delete = records_to_delete,
  arm_of_records_to_delete = arm_number
)

## End(Not run)
```



---

 redcap\_download\_file\_oneshot

*Download a file from a REDCap project record*


---

## Description

This function uses REDCap's API to download a file.

## Usage

```
redcap_download_file_oneshot(
  file_name = NULL,
  directory = NULL,
  overwrite = FALSE,
  redcap_uri,
  token,
  record,
  field,
  event = "",
  repeat_instrument = NULL,
  repeat_instance = NULL,
  verbose = TRUE,
  config_options = NULL
)
```

## Arguments

file_name	The name of the file where the downloaded file is saved. If empty the original name of the file will be used and saved in the default directory. Optional.
directory	The directory where the file is saved. By default current directory. Optional
overwrite	Boolean value indicating if existing files should be overwritten. Optional
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
record	The record ID where the file is to be imported. Required
field	The name of the field where the file is saved in REDCap. Required
event	The name of the event where the file is saved in REDCap. Optional
repeat_instrument	The name of the instrument that is repeating for a given event. Optional
repeat_instance	(only for projects with repeating instruments/events) The repeat instance number of the repeating event (if longitudinal) or the repeating instrument (if classic or longitudinal). Default value is '1'. Optional
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <a href="#">httr::POST()</a> method in the 'httr' package. See the details below. Optional.

## Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

## Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

## Author(s)

Will Beasley, John J. Aponte

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

## Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" #pid=213
record <- 1
field  <- "mugshot"
# event <- "" # only for longitudinal projects

result_1 <- REDCapR::redcap_download_file_oneshot(
  record      = record,
  field       = field,
  redcap_uri  = uri,
  token       = token
)
base::unlink("mugshot-1.jpg")
```

```

(full_name <- base::tempfile(pattern="mugshot", fileext=".jpg"))
result_2 <- REDCapR::redcap_download_file_oneshot(
  file_name = full_name,
  record    = record,
  field     = field,
  redcap_uri = uri,
  token     = token
)
base::unlink(full_name)

(relative_name <- "ssss.jpg")
result_3 <- REDCapR::redcap_download_file_oneshot(
  file_name = relative_name,
  record    = record,
  field     = field,
  redcap_uri = uri,
  token     = token
)
base::unlink(relative_name)

## End(Not run)

```

---

redcap\_download\_instrument

*Download REDCap Instruments*

---

## Description

Download instruments as a pdf, with or without responses.

## Usage

```

redcap_download_instrument(
  file_name = NULL,
  directory = NULL,
  overwrite = FALSE,
  redcap_uri,
  token,
  record = character(0),
  instrument = "",
  event = "",
  verbose = TRUE,
  config_options = NULL
)

```

## Arguments

file_name	The name of the file where the downloaded pdf is saved. Optional.
directory	The directory where the file is saved. By default current directory. Optional.

overwrite	Boolean value indicating if existing files should be overwritten. Optional.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
record	The record ID of the instrument(s). If empty, the responses are blank. Optional.
instrument	The instrument(s) to download. If empty, all instruments are returned. Optional.
event	The unique event name. For a longitudinal project, if record is not blank and event is blank, it will return data for all events from that record. If record is not blank and event is not blank, it will return data only for the specified event from that record. Optional.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details below. Optional.

### Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

### Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `record_id`: The `record_id` of the instrument.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

### Author(s)

Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```

## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" #pid=213
# event <- "" # only for longitudinal projects

(full_name <- base::temp(pattern="instruments-all-records-all", fileext=".pdf"))
result_1  <- REDCapR::redcap_download_instrument(
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)

(full_name <- base::tempfile(pattern="instruments-all-record-1-", fileext=".pdf"))
result_2  <- REDCapR::redcap_download_instrument(
  record       = 5,
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)
(full_name <- base::tempfile(pattern="instrument-1-record-1-", fileext=".pdf"))
result_3  <- REDCapR::redcap_download_instrument(
  record       = 5,
  instrument   = "health",
  file_name    = full_name,
  redcap_uri   = uri,
  token        = token
)
base::unlink(full_name)

## End(Not run)

```

---

redcap\_event\_instruments

*Enumerate the instruments to event mappings*

---

**Description**

Export the instrument-event mappings for a project (i.e., how the data collection instruments are designated for certain events in a longitudinal project). (Copied from "Export Instrument-Event Mappings" method of REDCap API documentation, v.10.5.1)

**Usage**

```

redcap_event_instruments(
  redcap_uri,
  token,

```

```

arms = c("1"),
verbose = TRUE,
config_options = NULL
)

```

### Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
arms	A character string of arms to retrieve. (Default: '1')
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

### Details

The full list of configuration options accepted by the `httr` package is viewable by executing [httr::httr\\_options\(\)](#). The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

### Value

Currently, a list is returned with the following elements,

- `data`: An R `base::data.frame()` where each row represents one column in the REDCap dataset.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Victor Castro, Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

### See Also

[redcap\\_instruments\(\)](#)

## Examples

```
## Not run:
uri          <- "https://bbmc.ouhsc.edu/redcap/api/"
token        <- "0434F0E9CF53ED0587847AB6E51DE762"
ds_event_instrument <- REDCapR::redcap_event_instruments(redcap_uri=uri, token=token)$data

## End(Not run)
```

---

redcap\_instruments      *Enumerate the instruments (forms)*

---

## Description

Export a list of the data collection instruments for a project. This includes their unique instrument name as seen in the second column of the Data Dictionary, as well as each instrument's corresponding instrument label, which is seen on a project's left-hand menu when entering data. The instruments will be ordered according to their order in the project. (Copied from "Export Instruments (Data Entry Forms)" method of REDCap API documentation, v.10.5.1)

## Usage

```
redcap_instruments(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

## Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

## Details

The full list of configuration options accepted by the `httr` package is viewable by executing [httr::httr\\_options\(\)](#). The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

## Value

Currently, a list is returned with the following elements,

- `data`: An R `base::data.frame()` where each row represents one column in the REDCap dataset.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.

- `outcome_message`: A human readable string indicating the operation's outcome.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Victor Castro, Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

### See Also

[redcap\\_event\\_instruments\(\)](#)

### Examples

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
ds_instrument <- REDCapR::redcap_instruments(redcap_uri=uri, token=token)$data

## End(Not run)
```

---

`redcap_metadata_read` *Export the metadata of a REDCap project*

---

### Description

Export the metadata (as a data dictionary) of a REDCap project as a `base::data.frame()`. Each row in the data dictionary corresponds to one field in the project's dataset.

### Usage

```
redcap_metadata_read(
  redcap_uri,
  token,
  forms = NULL,
  forms_collapsed = "",
  fields = NULL,
  fields_collapsed = "",
  verbose = TRUE,
  config_options = NULL
)
```



## Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
forms	An array, where each element corresponds to the REDCap form of the desired fields. Optional.
forms_collapsed	A single string, where the desired forms are separated by commas. Optional.
fields	An array, where each element corresponds to a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <a href="#">redcap_read_oneshot()</a> . Optional.

## Details

Specifically, it internally uses multiple calls to [redcap\\_read\\_oneshot\(\)](#) to select and return data. Initially, only primary key is queried through the REDCap API. The long list is then subsetted into partitions, whose sizes are determined by the `batch_size` parameter. REDCap is then queried for all variables of the subset's subjects. This is repeated for each subset, before returning a unified [base::data.frame\(\)](#).

The function allows a delay between calls, which allows the server to attend to other users' requests.

## Value

Currently, a list is returned with the following elements:

- `data`: An R [base::data.frame\(\)](#) of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_codes`: A collection of [http status codes](#), separated by semicolons. There is one code for each batch attempted.
- `outcome_messages`: A collection of human readable strings indicating the operations' semicolons. There is one code for each batch attempted. In an unsuccessful operation, it should contain diagnostic information.
- `forms_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `elapsed_seconds`: The duration of the function.

## Author(s)

Will Beasley

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

## Examples

```
## Not run:
uri  <- "https://bbmc.ouhsc.edu/redcap/api/"
token <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_metadata_read(redcap_uri=uri, token=token)

## End(Not run)
```

---

redcap\_metadata\_write *Import metadata of a REDCap project*

---

## Description

Import metadata (*i.e.*, data dictionary) into a project. Because of this method's destructive nature, it works for only projects in Development status.

## Usage

```
redcap_metadata_write(
  ds,
  redcap_uri,
  token,
  verbose = TRUE,
  config_options = NULL
)
```

## Arguments

ds	The <code>base::data.frame()</code> to be imported into the REDCap project. Required.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details in <code>redcap_read_oneshot()</code> Optional.

**Value**

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `field_count`: Number of fields imported.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

**Author(s)**

Will Beasley

**References**

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki. If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
# Please don't run this example without changing the token to
# point to your server. It could interfere with our testing suite.
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "457C24AB91B7FCF5B1A7DA67E70E24C7"

# Read in the dictionary in R's memory from a csv file.
ds_to_write <-
  readr::read_csv(
    file = system.file(
      "test-data/project-simple/simple-metadata.csv",
      package = "REDCapR"
    ),
    col_types = readr::cols(.default = readr::col_character())
  )
ds_to_write

# Import the dictionary into the REDCap project
REDCapR::redcap_metadata_write(
  ds      = ds_to_write,
  redcap_uri = uri,
  token    = token
)

## End(Not run)
```

---

`redcap_next_free_record_name`*Determine free available record ID*

---

### Description

Determines the next available record ID.

### Usage

```
redcap_next_free_record_name(  
  redcap_uri,  
  token,  
  verbose = TRUE,  
  config_options = NULL  
)
```

### Arguments

<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>verbose</code>	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
<code>config_options</code>	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

### Details

If the API call is unsuccessful, a value of `character(0)` will be returned (*i.e.*, an empty vector). This ensures that a the function will always return an object of class `base::character`.

### Value

a `base::character` vector of either length 1 (if successful) or length 0 (if not successful).

### Note

#### Documentation in REDCap 8.4.0

To be used by projects with record auto-numbering enabled, this method exports the next potential record ID for a project. It generates the next record name by determining the current maximum numerical record ID and then incrementing it by one.

Note: This method does not create a new record, but merely determines what the next record name would be.

If using Data Access Groups (DAGs) in the project, this method accounts for the special formatting of the record name for users in DAGs (e.g., DAG-ID); in this case, it only assigns the next value for ID for all numbers inside a DAG. For example, if a DAG has a corresponding DAG number of 223 wherein records 223-1 and 223-2 already exist, then the next record will be 223-3 if the API user belongs to the DAG that has DAG number 223. (The DAG number is auto-assigned by REDCap for each DAG when the DAG is first created.)

When generating a new record name in a DAG, the method considers all records in the entire project when determining the maximum record ID, including those that might have been originally created in that DAG but then later reassigned to another DAG.

Note: This method functions the same even for projects that do not have record auto-numbering enabled.

### Examples

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
# Returns 6
REDCapR::redcap_next_free_record_name(redcap_uri = uri, token = token)
```

---

redcap\_project

*A Reference Class to make later calls to REDCap more convenient*

---

### Description

This Reference Class represents a REDCap project. Once some values are set that are specific to a REDCap project (such as the URI and token), later calls are less verbose (such as reading and writing data).

### Fields

`redcap_uri` The URI (uniform resource identifier) of the REDCap project. Required.  
`token` token The user-specific string that serves as the password for a project. Required.

### Methods

`read(batch_size = 100L, interbatch_delay = 0, records = NULL, records_collapsed = "", fields = NULL, field`  
 Exports records from a REDCap project.

`write(ds_to_write, batch_size = 100L, interbatch_delay = 0, continue_on_error = FALSE, verbose = TRUE, co`  
 Imports records to a REDCap project.

**Examples**

```

uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "D70F9ACD1EDD6F151C6EA78683944E98"
## Not run:
project  <- REDCapR::redcap_project$new(redcap_uri=uri, token=token)
ds_all   <- project$read()

# Demonstrate how repeated calls are more concise when the token and
# url aren't always passed.
ds_skinny <- project$read(fields=c("record_id", "sex", "height"))$data

ids_of_males   <- ds_skinny$record_id[ds_skinny$sex==1]
ids_of_shorties <- ds_skinny$record_id[ds_skinny$height < 40]

ds_males       <- project$read(records=ids_of_males, batch_size=2)$data
ds_shorties    <- project$read(records=ids_of_shorties)$data

#Switch the Genders
sex_original   <- ds_skinny$sex
ds_skinny$sex  <- (1 - ds_skinny$sex)
project$write(ds_skinny)

#Switch the Genders back
ds_skinny$sex  <- sex_original
project$write(ds_skinny)

## End(Not run)

```

---

redcap_read	<i>Read records from a REDCap project in subsets, and stacks them together before returning a dataset</i>
-------------	---

---

**Description**

From an external perspective, this function is similar to `redcap_read_oneshot()`. The internals differ in that `redcap_read` retrieves subsets of the data, and then combines them before returning (among other objects) a single `base::data.frame()`. This function can be more appropriate than `redcap_read_oneshot()` when returning large datasets that could tie up the server.

**Usage**

```

redcap_read(
  batch_size = 100L,
  interbatch_delay = 0.5,
  continue_on_error = FALSE,
  redcap_uri,
  token,
  records = NULL,
  records_collapsed = "",

```

```

fields = NULL,
fields_collapsed = "",
forms = NULL,
forms_collapsed = "",
events = NULL,
events_collapsed = "",
raw_or_label = "raw",
raw_or_label_headers = "raw",
export_checkbox_label = FALSE,
export_survey_fields = FALSE,
export_data_access_groups = FALSE,
filter_logic = "",
datetime_range_begin = as.POSIXct(NA),
datetime_range_end = as.POSIXct(NA),
col_types = NULL,
guess_type = TRUE,
guess_max = NULL,
http_response_encoding = "UTF-8",
locale = readr::default_locale(),
verbose = TRUE,
config_options = NULL,
id_position = 1L
)

```

## Arguments

<code>batch_size</code>	The maximum number of subject records a single batch should contain. The default is 100.
<code>interbatch_delay</code>	The number of seconds the function will wait before requesting a new subset from REDCap. The default is 0.5 seconds.
<code>continue_on_error</code>	If an error occurs while reading, should records in subsequent batches be attempted. The default is FALSE, which prevents subsequent batches from running. Required.
<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>records</code>	An array, where each element corresponds to the ID of a desired record. Optional.
<code>records_collapsed</code>	A single string, where the desired ID values are separated by commas. Optional.
<code>fields</code>	An array, where each element corresponds to a desired project field. Optional.
<code>fields_collapsed</code>	A single string, where the desired field names are separated by commas. Optional.
<code>forms</code>	An array, where each element corresponds to a desired project form. Optional.

forms_collapsed	A single string, where the desired form names are separated by commas. Optional.
events	An array, where each element corresponds to a desired project event. Optional.
events_collapsed	A single string, where the desired event names are separated by commas. Optional.
raw_or_label	A string (either 'raw' or 'label' that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_checkbox_label	specifies the format of checkbox field values specifically when exporting the data as labels. If raw_or_label is 'label' and export_checkbox_label is TRUE, the values will be the text displayed to the users. Otherwise, the values will be 0/1.
export_survey_fields	A boolean that specifies whether to export the survey identifier field (e.g., 'redcap_survey_identifier') or survey timestamp fields (e.g., instrument+'_timestamp'). The timestamp outputs reflect the survey's <i>completion</i> time (according to the time and timezone of the REDCap server.)
export_data_access_groups	A boolean value that specifies whether or not to export the redcap_data_access_group field when data access groups are utilized in the project. Default is FALSE. See the details below.
filter_logic	String of logic text (e.g., [gender] = 'male') for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as TRUE. A blank/empty string returns all records.
datetime_range_begin	To return only records that have been created or modified <i>after</i> a given datetime, provide a <b>POSIXct</b> value. If not specified, REDCap will assume no begin time.
datetime_range_end	To return only records that have been created or modified <i>before</i> a given datetime, provide a <b>POSIXct</b> value. If not specified, REDCap will assume no end time.
col_types	A <code>readr::cols()</code> object passed internally to <code>readr::read_csv()</code> . Optional.
guess_type	A boolean value indicating if all columns should be returned as character. If true, <code>readr::read_csv()</code> guesses the intended data type for each column.
guess_max	Deprecated.
http_response_encoding	The encoding value passed to <code>httr::content()</code> . Defaults to 'UTF-8'.
locale	a <code>readr::locale()</code> object to specify preferences like number, date, and time formats. This object is passed to <code>readr::read_csv()</code> . Defaults to <code>readr::default_locale()</code> .



verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <code>redcap_read_oneshot()</code> Optional.
id_position	The column position of the variable that unique identifies the subject (typically <code>record_id</code> ). This defaults to the first variable in the dataset.

## Details

`redcap_read()` internally uses multiple calls to `redcap_read_oneshot()` to select and return data. Initially, only the primary key is queried through the REDCap API. The long list is then subsetted into batches, whose sizes are determined by the `batch_size` parameter. REDCap is then queried for all variables of the subset's subjects. This is repeated for each subset, before returning a unified `base::data.frame()`.

The function allows a delay between calls, which allows the server to attend to other users' requests (such as the users entering data in a browser). In other words, a delay between batches does not bog down the webserver when exporting/importing a large dataset.

A second benefit is less RAM is required on the webserver. Because each batch is smaller than the entire dataset, the webserver tackles more manageably sized objects in memory. Consider batching if you encounter the error:

```
ERROR: REDCap ran out of server memory. The request cannot be processed.  
Please try importing/exporting a smaller amount of data.
```

For `redcap_read()` to function properly, the user must have Export permissions for the 'Full Data Set'. Users with only 'De-Identified' export privileges can still use `redcap_read_oneshot`. To grant the appropriate permissions:

- go to 'User Rights' in the REDCap project site,
- select the desired user, and then select 'Edit User Privileges',
- in the 'Data Exports' radio buttons, select 'Full Data Set'.

## Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_codes`: A collection of `http status codes`, separated by semicolons. There is one code for each batch attempted.
- `outcome_messages`: A collection of human readable strings indicating the operations' semicolons. There is one code for each batch attempted. In an unsuccessful operation, it should contain diagnostic information.
- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.

- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.

### Author(s)

Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

### Examples

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_read(batch_size=2, redcap_uri=uri, token=token)$data

# Specify the column types.
col_types <- readr::cols(
  record_id = readr::col_integer(),
  race___1  = readr::col_logical(),
  race___2  = readr::col_logical(),
  race___3  = readr::col_logical(),
  race___4  = readr::col_logical(),
  race___5  = readr::col_logical(),
  race___6  = readr::col_logical()
)
REDCapR::redcap_read(
  redcap_uri = uri,
  token      = token,
  col_types  = col_types,
  batch_size = 2
)$data

## End(Not run)
```

---

redcap\_read\_oneshot    *Read/Export records from a REDCap project*

---

### Description

This function uses REDCap's API to select and return data.

**Usage**

```

redcap_read_oneshot(
  redcap_uri,
  token,
  records = NULL,
  records_collapsed = "",
  fields = NULL,
  fields_collapsed = "",
  forms = NULL,
  forms_collapsed = "",
  events = NULL,
  events_collapsed = "",
  raw_or_label = "raw",
  raw_or_label_headers = "raw",
  export_checkbox_label = FALSE,
  export_survey_fields = FALSE,
  export_data_access_groups = FALSE,
  filter_logic = "",
  datetime_range_begin = as.POSIXct(NA),
  datetime_range_end = as.POSIXct(NA),
  col_types = NULL,
  guess_type = TRUE,
  guess_max = 1000L,
  http_response_encoding = "UTF-8",
  locale = readr::default_locale(),
  verbose = TRUE,
  config_options = NULL
)

```

**Arguments**

<code>redcap_uri</code>	The URI (uniform resource identifier) of the REDCap project. Required.
<code>token</code>	The user-specific string that serves as the password for a project. Required.
<code>records</code>	An array, where each element corresponds to the ID of a desired record. Optional.
<code>records_collapsed</code>	A single string, where the desired ID values are separated by commas. Optional.
<code>fields</code>	An array, where each element corresponds to a desired project field. Optional.
<code>fields_collapsed</code>	A single string, where the desired field names are separated by commas. Optional.
<code>forms</code>	An array, where each element corresponds to a desired project form. Optional.
<code>forms_collapsed</code>	A single string, where the desired form names are separated by commas. Optional.
<code>events</code>	An array, where each element corresponds to a desired project event. Optional.

events_collapsed	A single string, where the desired event names are separated by commas. Optional.
raw_or_label	A string (either 'raw' or 'label') that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_checkbox_label	specifies the format of checkbox field values specifically when exporting the data as labels. If raw_or_label is 'label' and export_checkbox_label is TRUE, the values will be the text displayed to the users. Otherwise, the values will be 0/1.
export_survey_fields	A boolean that specifies whether to export the survey identifier field (e.g., 'redcap_survey_identifier') or survey timestamp fields (e.g., instrument+'_timestamp'). The timestamp outputs reflect the survey's <i>completion</i> time (according to the time and timezone of the REDCap server.)
export_data_access_groups	A boolean value that specifies whether or not to export the redcap_data_access_group field when data access groups are utilized in the project. Default is FALSE. See the details below.
filter_logic	String of logic text (e.g., [gender] = 'male') for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as TRUE. An blank/empty string returns all records.
datetime_range_begin	To return only records that have been created or modified <i>after</i> a given datetime, provide a <b>POSIXct</b> value. If not specified, REDCap will assume no begin time.
datetime_range_end	To return only records that have been created or modified <i>before</i> a given datetime, provide a <b>POSIXct</b> value. If not specified, REDCap will assume no end time.
col_types	A <code>readr::cols()</code> object passed internally to <code>readr::read_csv()</code> . Optional.
guess_type	A boolean value indicating if all columns should be returned as character. If false, <code>readr::read_csv()</code> guesses the intended data type for each column. Ignored if col_types is not null.
guess_max	A positive integer passed to <code>readr::read_csv()</code> that specifies the maximum number of records to use for guessing column types.
http_response_encoding	The encoding value passed to <code>httr::content()</code> . Defaults to 'UTF-8'.
locale	a <code>readr::locale()</code> object to specify preferences like number, date, and time formats. This object is passed to <code>readr::read_csv()</code> . Defaults to <code>readr::default_locale()</code> .
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (e.g. PHI), so turn this off if the output might be visible somewhere public. Optional.

`config_options` A list of options to pass to POST method in the `httr` package. See the details below. Optional.

### Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

If you do not pass in this `export_data_access_groups` value, it will default to `FALSE`. The following is from the API help page for version 10.5.1: *This flag is only viable if the user whose token is being used to make the API request is **not** in a data access group. If the user is in a group, then this flag will revert to its default value.*

### Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

### Examples

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"

#Return all records and all variables.
ds <- REDCapR::redcap_read_oneShot(redcap_uri=uri, token=token)$data
```

```

#Return only records with IDs of 1 and 3
desired_records_v1 <- c(1, 3)
ds_some_rows_v1 <- REDCapR::redcap_read_one-shot(
  redcap_uri = uri,
  token      = token,
  records    = desired_records_v1
)$data

#Return only the fields record_id, name_first, and age
desired_fields_v1 <- c("record_id", "name_first", "age")
ds_some_fields_v1 <- REDCapR::redcap_read_one-shot(
  redcap_uri = uri,
  token      = token,
  fields     = desired_fields_v1
)$data

# Specify the column types.
col_types <- readr::cols(
  record_id = readr::col_integer(),
  race___1  = readr::col_logical(),
  race___2  = readr::col_logical(),
  race___3  = readr::col_logical(),
  race___4  = readr::col_logical(),
  race___5  = readr::col_logical(),
  race___6  = readr::col_logical()
)
ds_col_types <- REDCapR::redcap_read_one-shot(
  redcap_uri = uri,
  token      = token,
  col_types  = col_types
)$data

## End(Not run)

```

---

```
redcap_read_one-shot_eav
```

*Read/Export records from a REDCap project –still in development*

---

## Description

This function uses REDCap's API to select and return data. This function is still in development.

## Usage

```
redcap_read_one-shot_eav(
  redcap_uri,
  token,
```

```

records = NULL,
records_collapsed = "",
fields = NULL,
fields_collapsed = "",
forms = NULL,
forms_collapsed = "",
events = NULL,
events_collapsed = "",
raw_or_label = "raw",
raw_or_label_headers = "raw",
export_data_access_groups = FALSE,
filter_logic = "",
datetime_range_begin = as.POSIXct(NA),
datetime_range_end = as.POSIXct(NA),
verbose = TRUE,
config_options = NULL
)

```

### Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
records	An array, where each element corresponds to the ID of a desired record. Optional.
records_collapsed	A single string, where the desired ID values are separated by commas. Optional.
fields	An array, where each element corresponds to a desired project field. Optional.
fields_collapsed	A single string, where the desired field names are separated by commas. Optional.
forms	An array, where each element corresponds to a desired project field. Optional.
forms_collapsed	A single string, where the desired form names are separated by commas. Optional.
events	An array, where each element corresponds to a desired project event. Optional.
events_collapsed	A single string, where the desired event names are separated by commas. Optional.
raw_or_label	A string (either 'raw' or 'label' that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_data_access_groups	A boolean value that specifies whether or not to export the redcap_data_access_group field when data access groups are utilized in the project. Default is FALSE. See the details below.

<code>filter_logic</code>	String of logic text (e.g., <code>[gender] = 'male'</code> ) for filtering the data to be returned by this API method, in which the API will only return the records (or record-events, if a longitudinal project) where the logic evaluates as TRUE. An blank/empty string returns all records.
<code>datetime_range_begin</code>	To return only records that have been created or modified <i>after</i> a given datetime, provide a <a href="https://stat.ethz.ch/R-manual/R-devel/library/base/html/as.POSIXlt.html">POSIXct</a> value. If not specified, REDCap will assume no begin time.
<code>datetime_range_end</code>	To return only records that have been created or modified <i>before</i> a given datetime, provide a <a href="https://stat.ethz.ch/R-manual/R-devel/library/base/html/as.POSIXlt.html">POSIXct</a> value. If not specified, REDCap will assume no end time.
<code>verbose</code>	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information (e.g. PHI), so turn this off if the output might be visible somewhere public. Optional.
<code>config_options</code>	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

## Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

If you do not pass in this `export_data_access_groups` value, it will default to FALSE. The following is from the API help page for version 5.2.3: This flag is only viable if the user whose token is being used to make the API request is *not* in a data access group. If the user is in a group, then this flag will revert to its default value.

As of REDCap 6.14.3, this field is not exported in the EAV API call.

## Value

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_collapsed`: The desired records IDs, collapsed into a single string, separated by commas.
- `fields_collapsed`: The desired field names, collapsed into a single string, separated by commas.
- `filter_logic`: The filter statement passed as an argument.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.



**Author(s)**

Will Beasley

**References**

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"

#Return all records and all variables.
ds <- REDCapR::redcap_read_oneshot_eav(redcap_uri=uri, token=token)$data

#Return only records with IDs of 1 and 3
desired_records_v1 <- c(1, 3)
ds_some_rows_v1    <- REDCapR::redcap_read_oneshot_eav(
  redcap_uri = uri,
  token      = token,
  records    = desired_records_v1
)$data

#Return only the fields record_id, name_first, and age
desired_fields_v1 <- c("record_id", "name_first", "age")
ds_some_fields_v1 <- redcap_read_oneshot_eav(
  redcap_uri = uri,
  token      = token,
  fields     = desired_fields_v1
)$data

## End(Not run)
```

---

`redcap_report`*Read/Export records that populate a REDCap report*

---

**Description**

Exports the data set of a report created on a project's 'Data Exports, Reports, and Stats' page.

**Usage**

```
redcap_report(
  redcap_uri,
  token,
```

```

report_id,
raw_or_label = "raw",
raw_or_label_headers = "raw",
export_checkbox_label = FALSE,
col_types = NULL,
guess_type = TRUE,
guess_max = 1000L,
verbose = TRUE,
config_options = NULL
)

```

## Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
report_id	A single integer, provided next to the report name on the report list page. Required.
raw_or_label	A string (either 'raw' or 'label') that specifies whether to export the raw coded values or the labels for the options of multiple choice fields. Default is 'raw'.
raw_or_label_headers	A string (either 'raw' or 'label' that specifies for the CSV headers whether to export the variable/field names (raw) or the field labels (label). Default is 'raw'.
export_checkbox_label	specifies the format of checkbox field values specifically when exporting the data as labels. If raw_or_label is 'label' and export_checkbox_label is TRUE, the values will be the text displayed to the users. Otherwise, the values will be 0/1.
col_types	A <code>readr::cols()</code> object passed internally to <code>readr::read_csv()</code> . Optional.
guess_type	A boolean value indicating if all columns should be returned as character. If false, <code>readr::read_csv()</code> guesses the intended data type for each column. Ignored if col_types is not null.
guess_max	A positive integer passed to <code>readr::read_csv()</code> that specifies the maximum number of records to use for guessing column types.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

## Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

**Value**

Currently, a list is returned with the following elements:

- `data`: An R `base::data.frame()` of the desired records and columns.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

**Author(s)**

Will Beasley

**References**

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
report_1_id <- 5980L
report_2_id <- 6431L

# Return all records and all variables.
ds_1a <-
  REDCapR::redcap_report(
    redcap_uri = uri,
    token      = token,
    report_id  = report_1_id
  )$data

# Specify the column types.
col_types_1 <- readr::cols(
  record_id      = readr::col_integer(),
  height         = readr::col_double(),
  health_complete = readr::col_integer(),
  address        = readr::col_character(),
  ethnicity      = readr::col_integer()
)
ds_1b <-
  REDCapR::redcap_report(
    redcap_uri = uri,
```

```

    token      = token,
    report_id  = report_1_id,
    col_types  = col_types_1
  )$data

# Return condensed checkboxes Report option:
# "Combine checkbox options into single column of only the checked-off
# options (will be formatted as a text field when exported to
# stats packages)"
col_types_2 <- readr::cols(
  record_id   = readr::col_integer(),
  race        = readr::col_character()
)
ds_2 <-
  REDCapR::redcap_report(
    redcap_uri = uri,
    token      = token,
    report_id  = report_2_id,
    col_types  = col_types_2
  )$data

## End(Not run)

```

---

redcap\_survey\_link\_export\_oneshot

*Download a file from a REDCap project record*

---

## Description

This function uses REDCap's API to download a file.

## Usage

```

redcap_survey_link_export_oneshot(
  redcap_uri,
  token,
  record,
  instrument,
  event = "",
  verbose = TRUE,
  config_options = NULL
)

```

## Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.

record	The record ID where the file is to be imported. Required
instrument	The name of the instrument associated with the survey link. Required
event	The name of the event where the file is saved in REDCap. Optional
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details below. Optional.

## Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

**Permissions Required** To use this method, you must have API Export privileges in the project. (As stated in the 9.0.0 documentation.)

## Value

Currently, a list is returned with the following elements,

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.
- `file_name`: The name of the file persisted to disk. This is useful if the name stored in REDCap is used (which is the default).

## Author(s)

Will Beasley

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "8FA9A6BDAE2C0B5DD3CB472DD8E8918C" #pid=817
record <- 1
instrument <- "participant_morale_questionnaire"
# event <- "" # only for longitudinal projects

result <- REDCapR::redcap_survey_link_export_oneshot(
  record      = record,
  instrument  = instrument,
  redcap_uri  = uri,
  token       = token
)
result$survey_link

## End(Not run)
```

---

redcap\_upload\_file\_oneshot

*Upload a file into to a REDCap project record*

---

**Description**

This function uses REDCap's API to upload a file.

**Usage**

```
redcap_upload_file_oneshot(
  file_name,
  record,
  redcap_uri,
  token,
  field,
  event = "",
  verbose = TRUE,
  config_options = NULL
)
```

**Arguments**

file_name	The name of the relative or full file to be uploaded into the REDCap project. Required.
record	The record ID where the file is to be imported. Required
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
field	The name of the field where the file is saved in REDCap. Required

event	The name of the event where the file is saved in REDCap. Optional
verbose	A boolean value indicating if messages should be printed to the R console during the operation. Optional.
config_options	A list of options to pass to POST method in the httr package. See the details below. Optional.

### Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See [validate\\_for\\_write\(\)](#) for a helper function that checks for some common important conflicts.

### Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Will Beasley, John J. Aponte

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (ie, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/456/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

### Examples

```
## Not run:
# Define some constants
uri    <- "https://bbmc.ouhsc.edu/redcap/api/"
token  <- "D70F9ACD1EDD6F151C6EA78683944E98" # The simple project -pid 213
field  <- "mugshot"
event  <- "" # only for longitudinal events

#Upload a single image file.
record  <- 1
file_path <- system.file("test-data/mugshot-1.jpg", package="REDCapR")
```

```

REDCapR::redcap_upload_file_oneshot(
  file_name = file_path,
  record    = record,
  field     = field,
  redcap_uri = redcap_uri,
  token     = token
)

#Upload a collection of five images.
records    <- 1:5
file_paths <- system.file(
  paste0("test-data/mugshot-", records, ".jpg"),
  package="REDCapR"
)

for (i in seq_along(records)) {
  record    <- records[i]
  file_path <- file_paths[i]
  REDCapR::redcap_upload_file_oneshot(
    file_name = file_path,
    record    = record,
    field     = field,
    redcap_uri = redcap_uri,
    token     = token
  )
}

## End(Not run)

```

---

redcap\_users\_export    *List authorized users*

---

### Description

List users authorized for a project.

### Usage

```
redcap_users_export(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

### Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the httr package. See the details below. Optional.



**Value**

a `utils::packageDescription`.

**Note****Documentation in REDCap 8.4.0**

This method allows you to export the list of users for a project, including their user privileges and also email address, first name, and last name.

Note: If the user has been assigned to a user role, it will return the user with the role's defined privileges.

**Examples**

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "06DEFB601F9B46847DAA9DF0CFA951B4"
result   <- REDCapR::redcap_users_export(redcap_uri=uri, token=token)
result$data_user
result$data_user_form
```

---

redcap_variables	<i>Enumerate the exported variables</i>
------------------	---

---

**Description**

This function calls the 'exportFieldNames' function of the REDCap API.

**Usage**

```
redcap_variables(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

**Arguments**

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

## Details

The full list of configuration options accepted by the `httr` package is viewable by executing `httr::httr_options()`. The `httr` package and documentation is available at <https://cran.r-project.org/package=httr>.

As of REDCap version 6.14.2, three variable types are *not* returned in this call: calculated, file, and descriptive. All variables returned are writable/uploadable.

## Value

Currently, a list is returned with the following elements,

- `data`: An R `base::data.frame()` where each row represents one column in the REDCap dataset.
- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The `http status code` of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

## Author(s)

Will Beasley

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

## Examples

```
## Not run:
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
ds_variable <- REDCapR::redcap_variables(redcap_uri=uri, token=token)$data

## End(Not run)
```

---

redcap_version	<i>Determine version of REDCap instance</i>
----------------	---

---

## Description

This function uses REDCap's API to query its version.

## Usage

```
redcap_version(redcap_uri, token, verbose = TRUE, config_options = NULL)
```

## Arguments

redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details below. Optional.

## Details

If the API call is unsuccessful, a value of `base::package_version("0.0.0")` will be returned. This ensures that a the function will always return an object of class `base::numeric_version`. It guarantees the value can always be used in `utils::compareVersion()`.

## Value

a `utils::packageDescription`

## Examples

```
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "9A81268476645C4E5F03428B8AC3AA7B"
REDCapR::redcap_version(redcap_uri = uri, token = token)
```

---

redcap_write	<i>Write/Import records to a REDCap project</i>
--------------	---

---

### Description

This function uses REDCap's APIs to select and return data.

### Usage

```
redcap_write(
  ds_to_write,
  batch_size = 100L,
  interbatch_delay = 0.5,
  continue_on_error = FALSE,
  redcap_uri,
  token,
  overwrite_with_blanks = TRUE,
  convert_logical_to_integer = FALSE,
  verbose = TRUE,
  config_options = NULL
)
```

### Arguments

ds_to_write	The <code>base::data.frame()</code> to be imported into the REDCap project. Required.
batch_size	The maximum number of subject records a single batch should contain. The default is 100.
interbatch_delay	The number of seconds the function will wait before requesting a new subset from REDCap. The default is 0.5 seconds.
continue_on_error	If an error occurs while writing, should records in subsequent batches be attempted. The default is FALSE, which prevents subsequent batches from running. Required.
redcap_uri	The URI (uniform resource identifier) of the REDCap project. Required.
token	The user-specific string that serves as the password for a project. Required.
overwrite_with_blanks	A boolean value indicating if blank/NA values in the R <code>base::data.frame</code> will overwrite data on the server. This is the default behavior for REDCapR, which essentially deletes the cell's value. If FALSE, blank/NA values in the <code>base::data.frame</code> will be ignored. Optional.
convert_logical_to_integer	If TRUE, all <code>base::logical</code> columns in ds are cast to an integer before uploading to REDCap. Boolean values are typically represented as 0/1 in REDCap radio buttons. Optional.

verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to POST method in the <code>httr</code> package. See the details in <a href="#">redcap_read_oneshot()</a> . Optional.

## Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See [validate\\_for\\_write\(\)](#) for a helper function that checks for some common important conflicts.

For `redcap_write` to function properly, the user must have Export permissions for the 'Full Data Set'. Users with only 'De-Identified' export privileges can still use [redcap\\_write\\_oneshot\(\)](#). To grant the appropriate permissions:

- go to 'User Rights' in the REDCap project site,
- select the desired user, and then select 'Edit User Privileges',
- in the 'Data Exports' radio buttons, select 'Full Data Set'.

## Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.

## Author(s)

Will Beasley

## References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

## Examples

```
## Not run:
#Define some constants
uri      <- "https://bbmc.ouhsc.edu/redcap/api/"
token    <- "D70F9ACD1EDD6F151C6EA78683944E98"
```

```

# Read the dataset for the first time.
result_read1 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds1          <- result_read1$data
ds1$telephone

# Manipulate a field in the dataset in a VALID way
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

ds1 <- ds1[1:3, ]
ds1$age      <- NULL; ds1$bmi <- NULL #Drop the calculated fields before writing.
result_write <- REDCapR::redcap_write(ds1, redcap_uri=uri, token=token)

# Read the dataset for the second time.
result_read2 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds2          <- result_read2$data
ds2$telephone

# Manipulate a field in the dataset in an INVALID way. A US exchange can't be '111'.
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

# This next line will throw an error.
result_write <- REDCapR::redcap_write(ds1, redcap_uri=uri, token=token)
result_write$raw_text

## End(Not run)

```

---

redcap\_write\_oneshot *Write/Import records to a REDCap project*

---

## Description

This function uses REDCap's API to select and return data.

## Usage

```

redcap_write_oneshot(
  ds,
  redcap_uri,
  token,
  overwrite_with_blanks = TRUE,
  convert_logical_to_integer = FALSE,
  verbose = TRUE,
  config_options = NULL
)

```

## Arguments

**ds**                   The `base::data.frame()` to be imported into the REDCap project. Required.

**redcap\_uri**           The URI (uniform resource identifier) of the REDCap project. Required.

token	The user-specific string that serves as the password for a project. Required.
overwrite_with_blanks	A boolean value indicating if blank/NA values in the R <code>base::data.frame</code> will overwrite data on the server. This is the default behavior for REDCapR, which essentially deletes the cell's value. If FALSE, blank/NA values in the <code>base::data.frame</code> will be ignored. Optional.
convert_logical_to_integer	If TRUE, all <code>base::logical</code> columns in <code>ds</code> are cast to an integer before uploading to REDCap. Boolean values are typically represented as 0/1 in REDCap radio buttons. Optional.
verbose	A boolean value indicating if messages should be printed to the R console during the operation. The verbose output might contain sensitive information ( <i>e.g.</i> PHI), so turn this off if the output might be visible somewhere public. Optional.
config_options	A list of options to pass to <code>httr::POST()</code> method in the 'httr' package. See the details in <code>redcap_read_oneshot()</code> Optional.

### Details

Currently, the function doesn't modify any variable types to conform to REDCap's supported variables. See `validate_for_write()` for a helper function that checks for some common important conflicts.

### Value

Currently, a list is returned with the following elements:

- `success`: A boolean value indicating if the operation was apparently successful.
- `status_code`: The [http status code](#) of the operation.
- `outcome_message`: A human readable string indicating the operation's outcome.
- `records_affected_count`: The number of records inserted or updated.
- `affected_ids`: The subject IDs of the inserted or updated records.
- `elapsed_seconds`: The duration of the function.
- `raw_text`: If an operation is NOT successful, the text returned by REDCap. If an operation is successful, the `raw_text` is returned as an empty string to save RAM.

### Author(s)

Will Beasley

### References

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
## Not run:
#Define some constants
uri          <- "https://bbmc.ouhsc.edu/redcap/api/"
token       <- "D70F9ACD1EDD6F151C6EA78683944E98"

# Read the dataset for the first time.
result_read1 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds1          <- result_read1$data
ds1$telephone

# Manipulate a field in the dataset in a VALID way
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

ds1 <- ds1[1:3, ]
ds1$sage      <- NULL; ds1$bmi <- NULL #Drop the calculated fields before writing.
result_write  <- REDCapR::redcap_write_oneshot(ds=ds1, redcap_uri=uri, token=token)

# Read the dataset for the second time.
result_read2 <- REDCapR::redcap_read_oneshot(redcap_uri=uri, token=token)
ds2          <- result_read2$data
ds2$telephone

# Manipulate a field in the dataset in an INVALID way. A US exchange can't be '111'.
ds1$telephone <- paste0("(405) 321-000", seq_len(nrow(ds1)))

# This next line will throw an error.
result_write  <- REDCapR::redcap_write_oneshot(ds=ds1, redcap_uri=uri, token=token)
result_write$raw_text

## End(Not run)
```

---

```
replace_nas_with_explicit
```

*Create explicit factor level for missing values*

---

**Description**

Missing values are converted to a factor level. This explicit assignment can reduce the chances that missing values are inadvertently ignored. It also allows the presence of a missing to become a predictor in models.

**Usage**

```
replace_nas_with_explicit(
  scores,
  new_na_label = "Unknown",
  create_factor = FALSE,
  add_unknown_level = FALSE
)
```



**Arguments**

scores	An array of values, ideally either factor or character. Required
new_na_label	The factor label assigned to the missing value. Defaults to Unknown.
create_factor	Converts scores into a factor, if it isn't one already. Defaults to FALSE.
add_unknown_level	Should a new factor level be created? (Specify TRUE if it already exists.) Defaults to FALSE.

**Value**

An array of values, where the NA values are now a factor level, with the label specified by the new\_na\_label value.

**Note**

The create\_factor parameter is respected only if scores isn't already a factor. Otherwise, levels without any values would be lost.

A stop error will be thrown if the operation fails to convert all the NA values.

**Author(s)**

Will Beasley

**Examples**

```
library(REDCapR) #Load the package into the current R session.
```

---

retrieve_credential	<i>Read a token and other credentials from a (non-REDCap) database or file</i>
---------------------	--

---

**Description**

These functions are not essential to calling the REDCap API, but instead are functions that help manage tokens securely.

**Usage**

```
retrieve_credential_local(  
  path_credential,  
  project_id,  
  check_url          = TRUE,  
  check_username     = FALSE,  
  check_token_pattern = TRUE,  
  username           = NA_character_  
)
```

```

retrieve_credential_mssql(
  project_id,
  instance,
  dsn,
  channel = NULL
)

create_credential_local(
  path_credential
)

```

### Arguments

path_credential	The file path to the CSV containing the credentials. Required.
project_id	The ID assigned to the project withing REDCap. This allows the user to store tokens to multiple REDCap projects in one file. Required
check_url	A logical value indicates if the url in the credential file should be checked to have approximately the correct form. Defaults to TRUE. <a href="#">retrieve_credential_local()</a> .
check_username	A logical value indicates if the username in the credential file should be checked against the username returned by R. Defaults to FALSE.
check_token_pattern	A logical value indicates if the token in the credential file is a 32-character hexadecimal string. Defaults to FALSE.
username	A character value used to retrieve a credential. See the Notes below. Optional.
instance	The casual name associated with the REDCap instance on campus. This allows one credential system to accommodate multiple instances on campus. Required
dsn	A <b>DSN</b> on the local machine that points to the desired MSSQL database. Required.
channel	An <i>optional</i> connection handle as returned by <a href="#">DBI::dbConnect()</a> . See Details below. Optional.

### Details

If the database elements are created with the script provided in package's 'Security Database' vignette, the default values will work.

The `create_credential_local()` function copies a **static file** to the location specified in the `path_credential` argument. Each record represents one accessible project per user. Follow these steps to adapt to your desired REDCap project(s):

1. Modify the credential file for the REDCap API with a text editor like **Notepad++**, **Visual Studio Code**, or **nano**. Replace existing records with the information from your projects. Delete the remaining example records.
2. Make sure that the file (with the sensitive password-like) tokens is stored securely!
3. Contact your REDCap admin to request the URI & token and discuss institutional policies.

4. Ask your institution's IT security team for their recommendation
5. For more info, see <https://ouhscbbmc.github.io/REDCapR/articles/workflow-read.html> and <https://ouhscbbmc.github.io>
6. Double-check the file is secured and not accessible by other users.

## Value

A list of the following elements are returned from `retrieve_credential_local()` and `retrieve_credential_mssql()`:

- `redcap_uri`: The URI of the REDCap Server.
- `username`: Username.
- `project_id`: The ID assigned to the project within REDCap.
- `token`: The token to pass to the REDCap server
- `comment`: An optional string that is ignored by REDCapR but can be helpful for humans.

## Note

*Storing credentials on a server is preferred*

Although we strongly encourage storing all the tokens on a central server (*e.g.*, see the `retrieve_credential_mssql()` function and the "SecurityDatabase" vignette), there are times when this approach is not feasible and the token must be stored locally. Please contact us if your institution is using something other than SQL Server, and would like help adapting this approach to your infrastructure.

*Stored credentials locally*

When storing credentials locally, typically the credential file should be dedicated to just one user. Occasionally it makes sense to store tokens for multiple users –usually it's for the purpose of testing. The username field is connected only in the local credential file. It does not need to be the same as the official username in REDCap.

## Author(s)

Will Beasley

## Examples

```
# ---- Local File Example -----
path <- system.file("misc/example.credentials", package = "REDCapR")
(p1 <- REDCapR::retrieve_credential_local(path, 153L))
(p2 <- REDCapR::retrieve_credential_local(path, 212L))

## Not run:
# Create a skeleton of the local credential file to modify
path_demo <- base::tempfile(pattern = "temp", fileext = ".credentials")

create_credential_local(path_demo)

base::unlink(path_demo) # This is just a demo; don't delete the real file!

## End(Not run)
```

---

sanitize_token	<i>Validate and sanitize the user's REDCap token</i>
----------------	--

---

**Description**

Verifies the token is nonmissing and conforms to the legal pattern of a 32-character hexadecimal value. Each character must be an (a) digit 0-9, (b) uppercase letter A-F, or (c) lowercase letter a-f. #' Trailing line endings are removed.

**Usage**

```
sanitize_token(token)
```

**Arguments**

token	The REDCap token. Required.
-------	-----------------------------

**Value**

The token, without a terminal newline character.

**Note**

Contact your institution's REDCap administrator for more information about your project-specific token.

**Author(s)**

Hao Zhu, Benjamin Nutter, Will Beasley, Jordan Mark Barbone

**Examples**

```
secret_token_1 <- "12345678901234567890123456ABCDEF"  
secret_token_2 <- "12345678901234567890123456ABCDEF\n"  
secret_token_3 <- "12345678901234567890123456abcdef"  
REDCapR::sanitize_token(secret_token_1)  
REDCapR::sanitize_token(secret_token_2)  
REDCapR::sanitize_token(secret_token_3)
```

---

validate	<i>Inspect a dataset to anticipate problems before writing to a REDCap project</i>
----------	--

---

### Description

This set of functions inspect a `base::data.frame()` to anticipate problems before writing with REDCap's API.

### Usage

```
validate_for_write( d )

validate_no_logical( data_types, stop_on_error )

validate_field_names( field_names, stop_on_error = FALSE )

validate_field_names_collapsed( field_names_collapsed, stop_on_error = FALSE )
```

### Arguments

<code>data_types</code>	The data types of the <code>base::data.frame()</code> corresponding to the REDCap project.
<code>stop_on_error</code>	If TRUE, an error is thrown for violations. Otherwise, a dataset summarizing the problems is returned.
<code>d</code>	The <code>base::data.frame()</code> containing the dataset used to update the REDCap project.
<code>field_names</code>	The names of the fields/variables in the REDCap project. Each field is an individual element in the character vector.
<code>field_names_collapsed</code>	The names of the fields/variables in the REDCap project. All fields are combined in a single vector element, separated by commas.

### Details

All functions listed in the Usage section above inspect a specific aspect of the dataset. The `validate_for_write()` function executes all these individual validation checks. It allows the client to check everything with one call.

Currently it verifies that the dataset

- does not contain **logical** values (because REDCap typically wants 0/1 values instead of FALSE/TRUE).
- starts with a lowercase letter, and subsequent optional characters are a sequence of (a) lowercase letters, (b) digits 0-9, and/or (c) underscores. (The exact regex is `^[a-z][0-9a-z_]*$`.)

If you encounter additional types of problems when attempting to write to REDCap, please tell us by creating a **new issue**, and we'll incorporate a new validation check into this function.

**Value**

A `tibble::tibble()`, where each potential violation is a row. The two columns are:

- `field_name`: The name of the `base::data.frame()` that might cause problems during the upload.
- `field_index`: The position of the field. (For example, a value of '1' indicates the first column, while a '3' indicates the third column.)
- `concern`: A description of the problem potentially caused by the field.
- `suggestion`: A *potential* solution to the concern.

**Author(s)**

Will Beasley

**References**

The official documentation can be found on the 'API Help Page' and 'API Examples' pages on the REDCap wiki (*i.e.*, <https://community.projectredcap.org/articles/456/api-documentation.html> and <https://community.projectredcap.org/articles/462/api-examples.html>). If you do not have an account for the wiki, please ask your campus REDCap administrator to send you the static material.

**Examples**

```
d <- data.frame(
  record_id      = 1:4,
  flag_logical   = c(TRUE, TRUE, FALSE, TRUE),
  flag_Uppercase = c(4, 6, 8, 2)
)
REDCapR::validate_for_write(d = d)
```

# Index

`base::character`, 28  
`base::data.frame`, 52, 55  
`base::data.frame()`, 7, 9, 10, 12–14, 22–26, 30, 33, 37, 40, 43, 50, 52, 54, 61, 62  
`base::iconv()`, 13  
`base::logical`, 52, 55  
`base::numeric_version`, 51  
`base::package_version`, 8

`checkbox_choices (metadata_utilities)`, 9  
`checkbox_choices()`, 9  
`collapse_vector`, 4  
`constant`, 5  
`constant_to_access (constant)`, 5  
`constant_to_export_rights (constant)`, 5  
`constant_to_form_completion (constant)`, 5  
`constant_to_form_rights (constant)`, 5  
`create_batch_glossary`, 7  
`create_credential_local (retrieve_credential)`, 57

`DBI::dbConnect()`, 58

`httr::content()`, 8, 14, 32, 36  
`httr::httr_options()`, 22, 23, 37, 40, 42, 50  
`httr::POST()`, 17, 20, 26, 45, 55

`kernel_api`, 8

`metadata_utilities`, 9

`POSIXct`, 40

`readr::cols()`, 32, 36, 42  
`readr::default_locale()`, 14, 32, 36  
`readr::locale()`, 14, 32, 36  
`readr::read_csv()`, 14, 32, 36, 42  
`redcap_arm_export`, 11  
`redcap_column_sanitiz`, 12  
`redcap_dag_read`, 13  
`redcap_delete`, 15  
`redcap_download_file_oneshot`, 17  
`redcap_download_instrument`, 19  
`redcap_event_instruments`, 21  
`redcap_event_instruments()`, 24  
`redcap_instruments`, 23  
`redcap_instruments()`, 22  
`redcap_metadata_read`, 24  
`redcap_metadata_write`, 26  
`redcap_next_free_record_name`, 28  
`redcap_project`, 29  
`redcap_read`, 30  
`redcap_read()`, 7, 33  
`redcap_read_oneshot`, 34  
`redcap_read_oneshot()`, 11, 15, 25, 26, 30, 33, 53, 55  
`redcap_read_oneshot_eav`, 38  
`redcap_report`, 41  
`redcap_survey_link_export_oneshot`, 44  
`redcap_upload_file_oneshot`, 46  
`redcap_users_export`, 48  
`redcap_variables`, 49  
`redcap_version`, 51  
`redcap_write`, 52  
`redcap_write_oneshot`, 54  
`redcap_write_oneshot()`, 53  
`REDCapR (REDCapR-package)`, 3  
`REDCapR-package`, 3  
`regex_named_captures (metadata_utilities)`, 9  
`regex_named_captures()`, 9  
`replace_nas_with_explicit`, 56  
`retrieve_credential`, 57  
`retrieve_credential_local (retrieve_credential)`, 57  
`retrieve_credential_local()`, 58  
`retrieve_credential_mssql (retrieve_credential)`, 57  
`sanitize_token`, 60

tibble, [11](#)  
tibble::tibble(), [62](#)

utils::compareVersion(), [8](#), [51](#)  
utils::packageDescription, [49](#), [51](#)  
utils::packageVersion, [8](#)

validate, [61](#)  
validate\_field\_names(validate), [61](#)  
validate\_field\_names\_collapsed  
  (validate), [61](#)  
validate\_for\_write(validate), [61](#)  
validate\_for\_write(), [18](#), [20](#), [45](#), [47](#), [53](#),  
  [55](#), [61](#)  
validate\_no\_logical(validate), [61](#)